

# ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	European Federation of Concrete Admixtures Associations a.i.s.b.l. (EFCA)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-EFC-20210196-IBG1-EN
Issue date	16.12.2021
Valid to	15.12.2026

**Concrete admixtures – Hardening Accelerators  
European Federation of Concrete  
Admixtures Associations a.i.s.b.l. (EFCA)**

[www.ibu-epd.com](http://www.ibu-epd.com) | <https://epd-online.com>



## 1. General Information

### European Federation of Concrete Admixtures Associations a.i.s.b.l. (EFCA)

#### Programme holder

IBU – Institut Bauen und Umwelt e.V.  
Panoramastr. 1  
10178 Berlin  
Germany

#### Declaration number

EPD-EFC-20210196-IBG1-EN

#### This declaration is based on the product category rules:

Concrete admixtures, 11.2017  
(PCR checked and approved by the SVR)

#### Issue date

16.12.2021

#### Valid to

15.12.2026



Dipl. Ing. Hans Peters  
(chairman of Institut Bauen und Umwelt e.V.)



Dr. Alexander Röder  
(Managing Director Institut Bauen und Umwelt e.V.)

### Concrete admixtures – hardening accelerators

#### Owner of the declaration

European Federation of Concrete Admixtures Associations a.i.s.b.l. (EFCA)  
Rue d'Arlon 55 BE-1040 Brussels, Belgium

#### Declared product / declared unit

1 kg of hardening accelerator, density: 1 - 1.6 kg/l

#### Scope:

This verified EPD entitles EFCA to bear the symbol of the Institut Bauen und Umwelt e.V. It exclusively applies for the product groups referred to for plants operated in Belgium, Finland, France, Germany, Italy, Netherlands, Norway, Poland, Spain, Sweden, Switzerland, Turkey and the United Kingdom by companies that are members of EFCA National Associations in these countries and for a period of five years from the date of issue. It involves a Model EPD where the product displaying the highest environmental impact in a group was selected for calculating the Life Cycle Assessment. Please refer to the EFCA website [www.efca.info](http://www.efca.info) for a list of National Associations.

The application of this EPD is only possible for member companies of EFCA's member associations and only for specific formulations with a total score below the declared maximum score for a product group according to the associated guidance document.


The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of *EN 15804+A2*. In the following, the standard will be simplified as *EN 15804*.

#### Verification

The standard *EN 15804* serves as the core PCR  
Independent verification of the declaration and data  
according to *ISO 14025:2010*

internally  externally



Matthias Schulz  
(Independent verifier)

## 2. Product

### 2.1 Information about the enterprise

EFCA (European Federation of Concrete Admixtures Associations) was formed in 1984 as a partnership between national admixture associations in order to promote the interests of the industry at European level. For more information (such as membership list) see: [www.efca.info](http://www.efca.info)

### 2.2 Product description/Product definition

Admixtures are liquid or powdery agents that are introduced in small amounts (< 5% by mass of the cement content) to concrete while it is being mixed and that enhance the properties of the fresh and/or hardened concrete.

Hardening accelerators are admixtures which accelerate the initial strength, with or without an influence on the setting time.

The results of the Life Cycle Assessment provided in this declaration have been selected from the product with the highest environmental impact (worst-case scenario).

The product needs a declaration of performance taking into consideration *EN 934-2:2009+A1:2012, Admixtures for concrete, mortar and grout – Part 2: Concrete admixtures – Definitions, requirements, conformity, marking and labelling* and the CE-marking. For the application and use the respective national provisions apply

### 2.3 Application

Concrete admixtures are used as constituent materials for the production of concrete, mortar and grout (unreinforced concrete, reinforced and prestressed concrete, site-mixed and ready-mixed concrete, precast concrete). Their application should be in line with the manufacturer's technical documents and Declaration of Performance.

### 2.4 Technical Data

Hardening accelerators must comply with the general requirements of *EN 934-1:2008* and the additional requirements of *EN 934-2:2009+A1:2012*. The corresponding requirements in line with *EN 934-1:2008* and *EN 934-2:2009+A1:2012* must be maintained.

#### Constructional data

Name	Value	Unit
Density /ISO 758/	1 - 1.6	g/ml
Solids content /EN 480-8/	- <sup>1</sup>	M.-%
pH value /ISO 4316/	- <sup>1</sup>	-log <sub>10</sub> (a <sub>H+</sub> )
Chloride content /EN 480-10/	Maximum value to be declared by the manufacturer	M.-%
Alkali content /EN 480-12/	Maximum value to be declared by the manufacturer	M.-%
Corrosion behavior /EN 934-1/, /EN 480-14/	- <sup>2</sup>	µ A/cm <sup>2</sup>
SiO <sub>2</sub> content /EN 192-2/	- <sup>3</sup>	M.-%
Air content of fresh concrete /EN 12350-7/	Test mix ≤ 2% by volume above the control mix unless stated otherwise by the manufacturer	Vol.-%
Compressive strength /EN 12390-3/	At 20 °C and 24 h: Test mix ≥ 120% of control mix At 20 °C and 28 days: Test mix ≥ 90% of control	N/mm <sup>2</sup>

	mix At 5 °C and 48 h: Test mix ≥ 130% of control mix	
Water reduction /EN 12350-2/, /EN 12350-5/ Plasticizer	- <sup>4</sup>	mm
Increasing / maintaining of consistence /EN 12350-2/, /EN 12350-5/ Superplasticizer	- <sup>4</sup>	mm
Setting time /EN 480-2/ Accelerator/Retarder	- <sup>4</sup>	min
Air void Characteristics in hardened concrete /EN 480-11/ Air entrainer	- <sup>4</sup>	mm
Capillary water absorption /EN 480-5/ Densifier	- <sup>4</sup>	g/mm <sup>2</sup>

<sup>1</sup> Value will be made available to user on request

<sup>2</sup> No corrosion behaviour test is required for admixtures which only contain active substances in the list of approved substances to *EN 934-1, Annexe A.1* and in the list of declared substances to *EN 934-1, Annexe A.2*.

<sup>3</sup> Maximum value must only be indicated when SiO<sub>2</sub> percentage by mass > 5 %

<sup>4</sup> Details not relevant for this type of admixture

Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to *EN 934-2:2009+A1:2012, Admixtures for concrete, mortar and grout – Part 2: Concrete admixtures – Definitions, requirements, conformity, marking and labelling*.

### 2.5 Delivery status

Hardening accelerators are usually supplied in liquid, paste or powder form in containers made of steel or plastic.

Typical container sizes are canisters containing approx. 25 kg, drums with approx. 200 kg or Intermediate Bulk Containers (IBC) with 1000 kg. The containers are shipped on wooden pallets.

For larger applications, loose deliveries in tank trucks with a capacity in excess of 1 tonne are also used.

### 2.6 Base materials/Ancillary materials

The main raw materials used for hardening accelerators are aluminium sulphate, formates, fluorides, aluminates, amorphous aluminium hydroxide, carbonates, silicates and ethanolamines. These raw materials are used on their own or in mixtures, in powder form or in aqueous solutions or as dispersions or suspensions. Apart from the raw materials referred to above, nitrates, nitrites and thiocyanates are also used.

Active substance concentration lies between 10 and 100% by mass. The typical dosage volumes for use in concrete are between 1 and 3% by mass, in terms of the cement weight.

The products covered by this EPD typically contain the following proportions by mass of constituent materials and auxiliaries referred to:

Aluminium sulphate*:	max. 70 %
Formates*:	max. 15 %
Aluminates*:	max. 50 %
Amorphous aluminium hydroxides*:	max. 20 %
Citrates*:	max. 50 %



Silicates*:	max. 2 %
Sulphates*:	max. 10 %
Ethanolamines*:	max. 10 %
Nitrates*:	max. 50 %
Org. acids*:	max. 10 %
Thiocyanates*:	max. 25 %
Additives:	max. 5 %
Water:	approx. 30 - 90 %

**\*Solid content**

These volumes are average values and the composition of products complying with the EPD can deviate from these concentration levels in individual cases.

*Note: For companies to declare their products within the scope of this EPD it is not sufficient to simply comply with the product composition shown above.*

*The application of this EPD is only possible for member companies of EFCA's member associations and only for specific formulations with a total score below the declared maximum score for a product group according to the associated guidance document. Concrete admixtures – hardening accelerators are mixtures under the chemical legislation (REACH and Classification Labelling and Packaging CLP).*

### 1. substances from the “Candidate List of Substances of Very High Concern for Authorisation” (SVHC)

If this product contains substances listed in the candidate list (latest version) exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD

If the construction product (concrete admixture hardening accelerators) contains SVHC exceeding 0.1 percentage by mass, the respective SVHC, its CAS number, information on the concentration and / or concentration range together with information on their hazardous properties are listed in the safety data sheet of the respective product.

### 2. CMR substances in categories 1A and 1B

If this product contains other carcinogenic, mutagenic, reprotoxic (CMR) substances in categories 1A or 1B which are not on the candidate list, exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD.

If the construction product (concrete admixture hardening accelerators) contains CMR substances in categories 1A or 1B exceeding 0.1 percentage by mass, the respective CMR substances, information on the concentration and/or concentration range together with information on their hazardous properties are listed in the safety data sheet of the respective product.

### 3. Biocide products added to the construction product

Biocide products were added to this construction product, or it has been treated with biocide products (this then concerns a treated product as defined by the (EU) Ordinance on Biocide Products No. 528/2012)

Usually the construction product (concrete admixture - hardening accelerators) contain small amounts (< 0.5% by mass) of biocides of the product type “in-can preservatives”.

The information which active substances are contained in the product can be found in the safety data sheet of the relevant product covered by this model EPD.

If the construction product (concrete admixture - hardening accelerators) contains biocide products, the active substances, information on the concentration and/or concentration range, the product type together with information on their hazardous properties are listed in the safety data sheet of the respective product.

#### 2.7 Manufacture

Concrete admixtures are usually manufactured by mixing ingredients (together) in batch mode and filling containers for dispatch. The process follows quality standards outlined in EN 934-6:2019.

#### 2.8 Environment and health during manufacturing

As a general rule, no environmental or health protection measures other than those specified by law are necessary.

#### 2.9 Product processing/Installation

During concrete manufacture, concrete admixtures are usually added along with the mixing water or included in premixed concrete.

Health and safety measures (eye protection, hand protection, possibly respiratory equipment and body protection) are to be taken and consistently adhered to in accordance with the information on the safety data sheet and conditions on site.

#### 2.10 Packaging

Reusable containers are, where practicable taken back by the manufacturer and redirected into the production circuit. Empty plastic or steel containers which can no longer be used are recyclable.

Wooden reusable pallets are, where practicable taken back by the manufacturer or building material trader who returns them to the building product manufacturer redirecting them into the production process.

#### 2.11 Condition of use

During the use phase, concrete admixtures are firmly bound into the cement matrix in hardened concrete. Concrete admixtures make an essential contribution towards optimizing the physical and chemical properties of concrete enhancing its performance, durability, economic value and sustainability.

#### 2.12 Environment and health during use

During the use phase, concrete admixtures are firmly bound into the cement matrix in hardened concrete. No relevant risks are known for water, air and soil if the products are used as designated.

#### 2.13 Reference service life

Not relevant as this declaration relates to a preliminary product.

#### 2.14 Extraordinary effects



**Fire**

Not relevant as this declaration relates to a preliminary product.

**Fire protection**

Not relevant as this declaration relates to a preliminary product .

**Water**

Not relevant as this declaration relates to a preliminary product.

**Mechanical destruction**

Not relevant as this declaration relates to a preliminary product.

**2.15 Re-use phase**

Not relevant as this declaration relates to a preliminary product.

**2.16 Disposal**

Empty, dried containers are directed to the recycling process where practicable.

Packaging residue must be directed to proper waste disposal taking local guidelines into consideration. Admixture residues, during the installation phase into the building, are directed to landfill. Admixture applied into the building and dismantled at the end of the product service life cannot be separated anymore from concrete. For this reason, this admixture is sent directly to landfill along with concrete. The European Waste Code (EWC) applicable for the declared product can be assimilated to the concrete EWC 170101.

**2.17 Further information**

More information is available in the manufacturers' product or safety data sheets on the manufacturers' Web sites or on request.

An electronic version of this declaration is available at [www.efca.info](http://www.efca.info) and [www.ibu-epd.com](http://www.ibu-epd.com)

**3. LCA: Calculation rules****3.1 Declared Unit**

This EPD refers to the declared unit of 1 kg concrete admixture applied into the building with a density of 1-1.6 kg/l in accordance with the IBU PCR 11.2017 Part B for concrete admixtures.

The maximum dosage of Hardening Accelerators is 3% by mass related to the cement content in the concrete.

The results of the Life Cycle Assessment provided in this declaration have been selected from the product with the highest environmental impact (worst-case scenario).

Depending on the application, a corresponding conversion factor such as the density to convert volumetric use to mass must be taken into consideration.

The Declaration type is according to *EN 15804*: Cradle to gate with options, modules C1–C4, and module D

**Declared unit**

Name	Value	Unit
Declared unit	1	kg
Gross density	1000 - 1600	kg/m <sup>3</sup>
Conversion factor to 1 kg	-	-

**3.2 System boundary**

Modules A1, A2 and A3 are taken into consideration in the LCA:

- A1 Production of preliminary products
- A2 Transport to the plant
- A3 Production incl. provision of energy, production of packaging as well as auxiliaries and consumables and waste treatment
- A5 Installation, admixtures applied into the building during A5 phase operations and packaging disposal.
- C1-C2-C4-D

The building deconstruction (demolition process) takes place in C1 module which considers energy production and consumption in terms of diesel and all the emissions connected with the fuel-burning process. After the demolition, admixture is transported to the end-of-life processing (C2 module) where all the

impacts related to the transport processes are considered. For precautionary principle and as worst-case scenario, disposal is the only end of life scenario considered. This is modelled by landfill process (module C4) where admixtures end their life cycle. Module D accounts for benefits that are beyond the defined system boundaries. Credits are generated during the incineration of wastes in module A5, which are declared in module D.

**3.3 Estimates and assumptions**

For this EPD formulation and production data defined by EFCA were considered. Production waste was assumed to be disposed of to landfill without credits as a worst case.

An average of plastic containers and wooden pallets was considered in the LCA.

**3.4 Cut-off criteria**

All raw materials submitted for the formulations and production data were taken into consideration. The manufacture of machinery, plant and other infrastructure required for production of the products under review was not taken into consideration in the LCA.

Transport of packaging materials is excluded.

**3.5 Background data**

Data from the *GaBi* database SP40 (2020) was used as background data.

**3.6 Data quality**

Representative products were applied for this EPD and the product in the group displaying the highest environmental impact was selected for calculating the LCA results. The background data sets used are no more than 4 years old.

Production data and packaging are based on details provided by the manufacturer. The formulation used for evaluation refers to a specific product.

The data quality of the background data is considered to be good.

**3.7 Period under review**

Representative formulations are valid for 2019 under consideration of data from 2011.



### 3.8 Allocation

Mass allocation have been applied when primary data have been used and implemented into the LCA model.

### 3.9 Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared

were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.

The *GaBi* database SP40 (2020) has been used..

## 4. LCA: Scenarios and additional technical information

### Characteristic product properties

#### Information on biogenic Carbon

The packaging material contains biogenic carbon content which has been presented below.

#### Information on describing the biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic Carbon Content in product	0.086	kg C
Biogenic Carbon Content in accompanying packaging	0.00071	kg C

Modules A1-A3, A5, C1, C2, C4 and D are declared.

#### Assembly (A5)

Name	Value	Unit
Other resources for packaging material	0.008	kg
Material loss	0.01	kg

Material loss regards the amount of admixture not used during the application phase into the building. This amount is 1 % of the admixture which is considered to come into module A5 phase. This admixture percentage is considered as waste to disposal and related impacts have been considered into the LCA model and allocated to A5.

#### End of life (C1-C4)

Name	Value	Unit
Collected as mixed construction waste	1	kg
Landfilling	1	kg

## 5. LCA: Results

Disclaimer:

EP-freshwater: This indicator has been calculated as “kg P eq” as required in the characterization model (EUTREND model, Struijs et al., 2009b, as implemented in ReCiPe; <http://eplca.jrc.ec.europa.eu/LCDN/developerEF.xhtml>)

**DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; ND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)**

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	ND	X	ND	ND	MNR	MNR	MNR	ND	ND	X	X	ND	X	X

**RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 kg hardening accelerator**

Core Indicator	Unit	A1-A3	A5	C1	C2	C4	D
Global warming potential - total	[kg CO <sub>2</sub> -Eq.]	1.79E+0	4.99E-2	2.79E-4	1.24E-2	2.93E-2	-1.41E-2
Global warming potential - fossil fuels	[kg CO <sub>2</sub> -Eq.]	2.08E+0	4.42E-2	2.66E-4	1.18E-2	1.52E-2	-1.40E-2
Global warming potential - biogenic	[kg CO <sub>2</sub> -Eq.]	-3.06E-1	5.71E-3	1.24E-5	5.42E-4	1.41E-2	-3.27E-5
GWP from land use and land use change	[kg CO <sub>2</sub> -Eq.]	5.91E-3	5.96E-5	6.39E-9	2.79E-7	4.37E-5	-9.62E-6
Depletion potential of the stratospheric ozone layer	[kg CFC11-Eq.]	3.91E-11	3.91E-13	2.84E-20	1.24E-18	5.62E-17	-1.43E-16
Acidification potential, accumulated exceedance	[mol H <sup>+</sup> -Eq.]	6.25E-3	7.02E-5	3.60E-6	3.73E-5	1.09E-4	-1.94E-5
Eutrophication, fraction of nutrients reaching freshwater end compartment	[kg PO <sub>4</sub> -Eq.]	5.97E-5	5.98E-7	5.75E-11	2.51E-9	2.61E-8	-1.77E-8
Eutrophication, fraction of nutrients reaching marine end compartment	[kg N-Eq.]	1.73E-3	1.98E-5	1.63E-6	1.72E-5	2.80E-5	-5.05E-6
Eutrophication, accumulated exceedance	[mol N-Eq.]	1.96E-2	2.33E-4	1.79E-5	1.89E-4	3.08E-4	-5.41E-5
Formation potential of tropospheric ozone photochemical oxidants	[kg NMVOC-Eq.]	3.59E-3	4.27E-5	4.91E-6	3.39E-5	8.48E-5	-1.45E-5
Abiotic depletion potential for non-fossil resources	[kg Sb-Eq.]	1.31E-6	1.31E-8	8.06E-12	3.52E-10	1.36E-9	-2.27E-9
Abiotic depletion potential for fossil resources	[MJ]	2.98E+1	3.07E-1	3.81E-3	1.66E-1	1.99E-1	-2.38E-1
Water (user) deprivation potential, deprivation-weighted water consumption (WDP)	[m <sup>3</sup> world-Eq deprived]	9.27E-1	1.30E-2	5.27E-7	2.30E-5	1.59E-3	-1.42E-3

**RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 kg hardening accelerator**

Indicator	Unit	A1-A3	A5	C1	C2	C4	D
Renewable primary energy as energy carrier	[MJ]	1.02E+1	1.32E-1	1.20E-5	5.25E-4	2.61E-2	-5.09E-2
Renewable primary energy resources as material utilization	[MJ]	2.86E-1	-2.60E-2	ND	ND	ND	ND
Total use of renewable primary energy resources	[MJ]	1.05E+1	1.06E-1	1.20E-5	5.25E-4	2.61E-2	-5.09E-2
Non-renewable primary energy as energy carrier	[MJ]	2.84E+1	5.67E-1	3.81E-3	1.67E-1	1.99E-1	-2.38E-1
Non-renewable primary energy as material utilization	[MJ]	1.42E+0	-2.60E-1	ND	ND	ND	ND
Total use of non-renewable primary energy resources	[MJ]	2.98E+1	3.07E-1	3.81E-3	1.67E-1	1.99E-1	-2.38E-1
Use of secondary material	[kg]	0.00E+0	ND	ND	ND	ND	ND
Use of renewable secondary fuels	[MJ]	0.00E+0	ND	ND	ND	ND	ND
Use of non-renewable secondary fuels	[MJ]	0.00E+0	ND	ND	ND	ND	ND
Use of net fresh water	[m <sup>3</sup> ]	5.17E-2	6.04E-4	2.16E-8	9.41E-7	5.02E-5	-5.89E-5

**RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 kg hardening accelerator**

Indicator	Unit	A1-A3	A5	C1	C2	C4	D
Hazardous waste disposed	[kg]	3.52E-7	3.53E-9	3.70E-13	1.62E-11	3.03E-9	-9.48E-11
Non-hazardous waste disposed	[kg]	3.98E-1	5.45E-3	3.90E-7	1.70E-5	1.00E+0	-1.09E-4
Radioactive waste disposed	[kg]	1.52E-3	1.56E-5	4.09E-9	1.79E-7	2.27E-6	-1.74E-5
Components for re-use	[kg]	0.00E+0	ND	ND	ND	ND	ND
Materials for recycling	[kg]	0.00E+0	ND	ND	ND	ND	ND
Materials for energy recovery	[kg]	0.00E+0	ND	ND	ND	ND	ND
Exported electrical energy	[MJ]	0.00E+0	5.81E-2	ND	ND	ND	ND
Exported thermal energy	[MJ]	0.00E+0	1.10E-1	ND	ND	ND	ND

**RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: 1 kg hardening accelerator**

Indicator	Unit	A1-A3	A5	C1	C2	C4	D
Potential incidence of disease due to PM emissions	[Disease Incidence]	ND	ND	ND	ND	ND	ND
Potential Human exposure efficiency relative to U235	[kBq U235-Eq.]	ND	ND	ND	ND	ND	ND
Potential comparative toxic unit for ecosystems	[CTUe]	ND	ND	ND	ND	ND	ND
Potential comparative toxic unit for humans - cancerogenic	[CTUh]	ND	ND	ND	ND	ND	ND
Potential comparative toxic unit for humans - not cancerogenic	[CTUh]	ND	ND	ND	ND	ND	ND
Potential soil quality index	[-]	ND	ND	ND	ND	ND	ND

Potential Human exposure efficiency relative to U235, Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and (from) some construction materials is also not measured by this indicator.

ADP minerals & metals, ADP fossil, WDP, ETF-fw, HTP-c, HTP-nc, SQP, Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

**Additional environmental impact indicators** (suggested by *EN15804*, table 4) are not declared in the EPD. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high and as there is limited experience with the indicator (see ILCD classification in *EN 15804*, table 5). For this reason, results based on these indicators are not considered suitable for a decision-making process and are thus not declared in the EPD.

## 6. LCA: Interpretation

When considering upstream production and transport of pre-products as well as manufacturing of the concrete admixture (modules A1-A3), the main driver of impacts in all categories is the production of pre-products (module A1), generally more than 90 %.

For global warming potential (GWP) about 90 % the impacts are from pre-products production processes and related chemical precursors. The manufacturing process is the second contributor (less than 10 % of the total GWP). Important contributors to this indicator during the manufacturing process are electricity production consumed during the admixture production process (module A3) like for thermal energy produced from natural gas combustion. European electricity grid mix has a minor contribution to all indicators. Generally, manufacturing has a very low contribution to all impacts.

The other life cycle phases have minor influence, generally lower than 4 %.

A5 module: It is mainly dominated by the incineration process of packaging wastes, in particular the incineration of plastic (HDPE) is the main contributor for all indicators followed by incineration of wood packaging. This module accounts also for the calorific value of the packaging considered as an output and

therefore with a negative value. This influences PENRM, non-renewable energy content by plastic packaging and PERM, renewable energy content by wood packaging.

Considering the entire end of life modules, landfill for construction wastes is the main contributor for all the impact considered, followed by the truck used for transporting the waste from the building site to the landfill.

C1 module: the combustion of fuel occurring during demolition processes is the main contributor for this module and for all the impacts considered.

C2 module: trucks used for waste transport and related combustion emissions are the main contributor for all impacts considered.

C3 module: landfill process and in particular energy consumed for landfill management and operation is the main contributor for all the impacts considered.

D module: It is influenced by the credits generated during implementation module (A5), thanks to the energy produced by the incineration processes used for packaging disposal and secondly by the incineration of the admixture residue when this material can be incinerated (thanks to its calorific value).

## 7. Requisite evidence

As this involves a declaration of preliminary products, special tests and evidence within the framework of drawing up this Model Environmental Product Declaration have not been carried out or provided.

## 8. References

### Candidate list





Candidate list List of those eligible for approval substances of very high concern to the European Chemicals Agency, as of July 2021.

#### **CLP**

Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures, as of February 03-2021

#### **CPR**

Construction Production Regulation (EU) No 305/2011 of the European Parliament and of the council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

#### **EN ISO 9001:2015**

EN ISO 9001:2015, Quality management systems – Requirements (ISO 9001:2015)[AR1]

#### **EN 196-2:2013**

EN 196-2:2013, Test methods for cement – Part 2: Chemical analysis of cement

#### **EN 206:2013+A1:2016**

EN 206:2013+A1:2016, Concrete – Part 1: Specification, performance, production and conformity

#### **EN 480-1:2014**

EN 480-1:2014, Admixtures for concrete, mortar and grout – Test methods – Part 1: Reference concrete and reference mortar for testing

#### **EN 480-2:2006**

EN 480-2:2006, Admixtures for concrete, mortar and grout – Test methods – Part 2: Determination of setting time

#### **EN 480-4:2005**

EN 480-4:2005, Admixtures for concrete, mortar and grout – Test methods – Part 4: Determination of bleeding of concrete

#### **EN 480-5:2005**

EN 480-5:2005, Admixtures for concrete, mortar and grout – Test methods – Part 5: Determination of capillary absorption

#### **EN 480-6:2005**

EN 480-6:2005, Admixtures for concrete, mortar and grout – Test methods – Part 6: Infra red analysis

#### **EN 480-8:2012**

EN 480-8:2012, Admixtures for concrete, mortar and grout – Test methods – Part 8: Determination of the conventional dry material content

#### **EN 480-10:2009**

EN 480-10:2009, Admixtures for concrete, mortar and grout – Test methods – Part 10: Determination of water-soluble chloride content

#### **EN 480-11:2005**

EN 480-11:2005, Admixtures for concrete, mortar and grout – Test methods - Part 11: Determination of air void characteristics in hardened concrete

#### **EN 480-12:2005**

EN 480-12:2005, Admixtures for concrete, mortar and grout – Test methods – Part 12: Determination of the alkali content of admixtures

#### **EN 480-14:2006**

EN 480-14:2006, Admixtures for concrete, mortar and grout – Test methods – Part 14: Determination of the effect on corrosion susceptibility of reinforcing steel by potentiostatic electro-chemical test

#### **EN 934-1:2008**

EN 934-1:2008, Admixtures for concrete, mortar and grout – Part 1: Common requirements

#### **EN 934-2:2009+A1:2012**

EN 934-2:2009+A1:2012, Admixtures for concrete, mortar and grout – Part 2: Concrete admixtures – Definitions, requirements, conformity, marking and labelling

#### **EN 934-5:2007**

EN 934-5:2007, Admixtures for concrete, mortar and grout – Part 5: Admixtures for sprayed concrete – Definitions, requirements, conformity, marking and labelling

#### **EN 934-6:2019**

EN 934-6:2019, Admixtures for concrete, mortar and grout – Part 6: Sampling, assessment and verification of the constancy of performance

#### **EN 12350-2:2019**

EN 12350-2:2019, Testing fresh concrete – Part 2: Slump test

#### **EN 12350-5:2019**

EN 12350-5:2019, Testing fresh concrete – Part 5: Flow table test

#### **EN 12350-7:2019**

EN 12350-7:2019, Testing fresh concrete – Part 7: Air content – Pressure methods

#### **EN 12390-3:2019**

EN 12390-3:2019, Testing hardened concrete – Part 3: Compressive strength of test specimens

#### **EN 14487-1:2005**

EN 14487-1:2005, Sprayed concrete – Part 1: Definitions, specifications and conformity

#### **EN 15804: 2012+A2:2019**

EN 15804: 2012+A2:2019, Sustainability of construction works -Environmental Product Declarations - Core rules for the product category of construction products

#### **EU Biocidal Products Regulation (No. 528/2012)**

The EU Biocidal Products Regulation (No. 528/2012) Guidance document for ASD industries (January 2016)

#### **EWC/AVV waste code**

Directive governing introduction of the European Waste Catalogue  
<http://www.ngs-mbh.de/zs/eak.html>

#### **GaBi 10 software & documentation**

Data base for Life Cycle Engineering LBP, University of Stuttgart and Sphera, documentation of GaBi 10



data sets <http://documentation.gabi-software.com/>, 2020

**IBU 2021**

Institut Bauen und Umwelt e.V.: General Instructions for the EPD programme of Institut Bauen und Umwelt e.V. EPD programme. Version 2.0. Berlin: Institut Bauen und Umwelt e.V., 2021  
[www.ibu-epd.com](http://www.ibu-epd.com)

**ISO 758:1976**

ISO 758:1976, Liquid chemical products for industrial purposes; Determination of density at 20 °C

**ISO 4316:1977**

ISO 4316:1977, Surface active agents; Determination of the pH value of aqueous solutions; Potentiometric method

**PCR Part A**

Product Category Rules for Building-Related Products and Services, Part A: Calculation Rules for the Life

Cycle Assessment and Requirements on the Project report, Version 1.1, Institut Bauen und Umwelt e.V., 2021-01

**PCR Part B**

Product Category Rules for Construction Products, Part B: Requirements on the EPD for concrete admixtures, 2017-11

**REACH Regulation**

Regulation (EU) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)  
[AR1]Please use this formatting for all standards quoted.

**Publisher**

Institut Bauen und Umwelt e.V.  
Panoramastr. 1  
10178 Berlin  
Germany

Tel +49 (0)30 3087748- 0  
Fax +49 (0)30 3087748- 29  
Mail [info@ibu-epd.com](mailto:info@ibu-epd.com)  
Web [www.ibu-epd.com](http://www.ibu-epd.com)

**Programme holder**

Institut Bauen und Umwelt e.V.  
Panoramastr 1  
10178 Berlin  
Germany

Tel +49 (0)30 - 3087748- 0  
Fax +49 (0)30 - 3087748 - 29  
Mail [info@ibu-epd.com](mailto:info@ibu-epd.com)  
Web [www.ibu-epd.com](http://www.ibu-epd.com)

**Author of the Life Cycle Assessment**

Sphera Solutions GmbH  
Hauptstraße 111- 113  
70771 Leinfelden-Echterdingen  
Germany

Tel +49 711 341817-0  
Fax +49 711 341817-25  
Mail [info@sphera.com](mailto:info@sphera.com)  
Web [www.sphera.com](http://www.sphera.com)

**Owner of the Declaration**

European Federation of Concrete  
Admixtures Associations a.i.s.b.l.  
(EFCA)  
Rue d'Arlon 55  
1040 Brussels  
Belgium

Tel -  
Fax -  
Mail [secretary@efca.info](mailto:secretary@efca.info)  
Web [www.efca.info](http://www.efca.info)